PEARLY HAZE (+)

SANDBLAST OPTIC | IN- AND OUTSIDE INSTALLATION

Very good privacy protection due to „sandblast optic“ with silvery Pearly Flakes. The film provides a very high level of privacy with low light loss. The film is suitable for full surface installation, as well as for finishing in digital printing or contour cutting with plotters. The film is available in two options. With air duct adhesive technology for bubble-free, fast dry installation, as well as with classic, full-surface adhesive.

DECORATIVE FILM

Physical Properties	
Base material	PVC (polymeric calendered)
Film thickness	approx. 75 µm
Light transmission	approx. 55 %
Adhesive	permanent, acrylic adhesive
Adhesion to glass (dry installation)	after 20 min: 15N/25mm after 24 h: 20N/25mm
Liner material	PE-coated paper
Temperature stability	-30° C to +90° C, installed
Dimensional stability (70° C, 48 h, installed on aluminum)	max. -0,50 %
Installation temperature	min. +8° C
Printability	☑ UV ☑ Latex ☑ (Eco-)Solvent

Material Construction Self Adhesive Film

- Translucent PVC film.
- Robust surface.
- Coated paper liner.
- High quality acrylate adhesive system (Variant „+“ with air channel – dry installation only!)

BRUXSAFOL Warranty 10 years inside installation
3 years outside installation, vertical installation*

Life span 5-7 years in outdoor installation*

Storage Recommended at +25° C and rel. humidity 50 %: approx. 2 years

Possible Widths ☑ 160 cm

Film-to-Glass Guide

Single pane clear or tinted	●
Double pane clear or tinted	●
Double pane Low-e on #2	●
Double pane Low-e on #3	●
Triple pane Low-e	▲

● Low risk
▲ Caution! Submit Film-to-Glass application for risk assessment.
■ Tempered only

For further details please view:
www.bruxsafol.de/download/ftg-guide.pdf

All rights and errors reserved. *Guarantee and life expectancy data refer to Central European climate. Technical data calculated using „Window 7.2.“ according to EN 410 and EN 673.

03/2025

BRUXSAFOL Folien GmbH · Thüringenstraße 2 · 97762 Hammelburg · **Tel. +49 97 32 / 78 73 - 0** · info@bruxsafol.com · **www.bruxsafol.com**