

# Care Instructions for Bruxsafol Architectural Films

BRUXSAFOL films have a scratch-resistant surface (except for matt and decorative films). This hardcoat withstands a standard cleaning process. Please note that this hardcoat does not reach the hardness of a normal pane of glass. Please find below, the care instructions for films with and without a hardcoat:

- Please avoid the use of acetone, lacquer thinner, paint thinner or ammonia based cleaner.
- Use only commercially available glass cleaners (item no. T21000) based on alcohol or mild soap solutions (e.g. applicator 2.0, item no. T22001).
- Never clean without liquid and never use abrasive cleaning agents!
- Do not use brushes, steel wool or abrasive cloths, do not rework dry!
- Always work with plenty of water, a soft, non-fluffy cloth or synthetic sponge, chamois leather and rubber squeegees (Art. No. T8000).

Cleaning should always be done with fresh water. This ensures that there are no particles such as dust or sand in the water that could scratch the film.

1. Spray the window surface with the water-cleaner mixture (e.g. BRUXSAFOL pressure spray bottle, item no. T20000). Alternatively you can use a synthetic sponge to wet the surface.
2. Remove the water with a rubber squeegee from top to bottom.
3. Soak heavily soiled areas again with soft chamois leather or sponge and plenty of water or the undiluted glass cleaner carefully.  
Never press hard!
4. Spray the window again with the water-cleaner mixture and remove the water again with a rubber squeegee from top to bottom.
5. Let dry or wipe lightly with damp chamois leather.



*If professional window cleaners are to clean the windows, be sure to give them these care instructions:*

## **Information for professional window cleaners**

If you use a squeegee with a stainless steel rubber holder to clean the window, we recommend that you attach the plastic end clips to the right and left edge of the rubber lip so that the ends of the holder do not damage the film.